

A2 -100%

Automatic Dispenser



➡ 100% Recirculation

➡ Box Tinting

SANTINT • CHINA

Address: Xushui Industrial Trade
Park, Zhengzhou.
Tel: +86 371 6785 7168

SANTINT • POLAND

Address: ul. Postepu 19. mag.5
02-676 Warszawa Polska
Email: info@santint.com

SANTINT • U.S.A

Address: 2000 Bloomingdale Road, Suite
220, Glendale Heights, IL 60139
Tel: +1 847 350 6911

SANTINT • AUSTRALIA


Address: 2/4 Weddel Court
Laverton North Victoria
Email: info@santint.com

A2-100% FEATURES >>>



1 100% Recirculation

Zero nozzle dryness/blockage;
purge-free;
maintenance-free;
colorant saving;
stable accuracy.



2 Box Tinting

Saving PC cost;
pre-installed software,
shorter installation time.




3 Calibration-free Piston Pump



4 Piston Rod Detection

Warning when the piston is not pushed down.



P1 Piston Pump
Sequential Dispensing

■ Flow Rate 600ml/min
■ Efficiency 200ml/min

■ Minimum Shot
1/384Y(0.077ml)

■ Pump Capacity 60ml
■ Stirring Speed 20rpm

■ No. of Canisters Up to 16
■ Canister Size 1.8 / 2.3L / 3.8L

■ Max Can Size (D X H) 320X600mm
■ Machine Dimension (W X D X H) 707X848X1300mm
■ Packing Dimension (W X D X H) 830X990X1500mm
Loading Quantity 14 Pieces/20"Container

■ Net Weight 140Kg
■ Gross Weight 165Kg
■ Power ≤ 100W
■ Power Supply 220V/110V 50Hz/60Hz

A2 - 100% Technical Parameters